

Square One

Technical Specifications

Construction & Materials

Blocks:	Blocks are manufactured using kiln-dried, solid European Beech and are attached using hardware, available in your choice of nickel or black, for durability and strength.
Finish:	Indiana Furniture uses a multi-step hand finishing process. Blocks are pre-sanded for smoothness, then stained and finished with a catalyzed varnish finish which offers durability, lasting beauty, and resistance to normal wear. Square One finishes were selected to complement casegoods, tables, and seating finishes which allows for easy blending of furniture.
End+Top Caps:	Measure 1¾"W and 1¾"D and come in a variety of lengths. Used vertically and horizontally to provide a clean, balanced aesthetic by hiding the attachment hardware. Caps are constructed of kiln-dried, solid European Beech and include blind threaded inserts for installation.
Corner Posts:	Measure 1¾"W and 1¾"D and come in a variety of heights. Used to create 90° turns. Corner posts are constructed of kiln-dried solid European Beech and include blind threaded inserts for installation.
T-Connectors:	Measure 1¾"W and 1¾"D and come in a variety of heights. Used vertically and horizontally to create an intersection for three wall runs. T-Connectors are constructed of kiln-dried, solid European Beech and include blind threaded inserts for installation.
X-Connectors:	Measure 1¾"W and 1¾"D and come in a variety of heights. Used vertically to create an intersection for four wall runs. X-Connectors are constructed of kiln-dried, solid European Beech and include blind threaded inserts for installation.
Horizontal Beam Spanners:	Measure 1¾"D and 1¾"H and come in a variety of widths. Used horizontally to provide structural support for doorways and other designed openings. Spanners are constructed of kiln-dried, solid European Beech and include blind threaded inserts for installation.
Dry Erase Boards:	Available in 22½" or 46½" heights and multiple widths. Installed onset, either vertically or horizontally. Installation brackets are included; longer bolts for installation on-site are also included.
Acoustical Panels:	Constructed of 100% polyester made from up to 50% recycled materials without the use of adhesive or other bonding agents, Acoustical Panels are 100% recyclable. Panels are ½" (12mm) thick and are available in multiple widths and lengths. Sound absorption is average NRC 0.75 (50mm air gap) 1.0 NRC in mid-high frequencies. Panels are installed inset with tabs or onset with dual-lock connectors.
Tackable Panels:	Tackable Panels are constructed of ¾" corkboard and then covered, on both sides, in the textile of your choice. Highly-skilled upholsterers hand tailor each unit to meet individual specifications. Upholstery options include a broad range of styles, all pregraded in this price list for ease of use. Panels are installed onset with dual-lock connectors.
Acrylic Inserts:	Acrylic inserts are manufactured using high performance engineering resins and provide translucency, strength, clarity, and versatility. Inserts are 20½"W and are available in 8½" and 20½" lengths. Inserts are inset within the blocks with retainers for a tight-fitting installation. Frosted acrylic options can be customized with logos and other designs as requested.
Barn Door:	Sliding system tracks are constructed of black powder coated steel. Hardware includes tracks, hangers, track stops, screws, inserts, bracket, and sliding system. Installation hardware will be shipped attached to components.
Leveling Glides:	Heavy-duty, adjustable leveling glides are available in black or nickel and are recommended to ensure proper leveling and compensation for uneven floors. A tool (6mm allen driver bit) to install glides is also available to ensure proper installation.
Planter Boxes:	The planter box is made of ¾" thick thermally-fused laminate (TFL) fused particle-board core. Grain direction runs horizontal. Planter boxes are fastened together with screws and heavyduty metal fasteners. Optional insert is made of lightweight, fade-resistant, recyclable plastic.
Warranty:	12 Year Warranty (some exclusions may apply, see Full Warranty in Price List).

Certifications & Compliance

- Intertek Sustainability Certified for compliance with VOC emission concentrations
- BIFMA level® Certified for environmentally-preferable and socially-responsible office furniture
- BIFMA Compliant® Certified for meeting mechanical standards that focus on safety and durability
- TSCA Title VI (Formerly CARB) Compliance
- Contribution to U.S. Green Building Council's LEED Program

