

Brea Guest

Technical Specifications

Construction & Materials

- Frame:** Exposed wood frames are manufactured using European Beech and are free of spirits, discoloration, pits, shakes, and wormholes; joints are double doweled, screwed, and glued for maximum strength and durability. Non-marring glides included with each leg.
- Seat:** High quality resilient sheet webbing paired with high-grade polyurethane foam, 2½" thick in the seat and 1½" thick in the back, ensure a comfortable seating application; corner blocking ensures sturdy support.
- Finish:** Multi-step catalyzed varnish hand-finishing process is used on all exposed wood frames.


Features

- The warmth of wood blends with supportive comfort in Brea to deliver an enduring design suited for a multitude of applications.
- Two arm and two back styles create a classic design suited for Traditional to Transitional spaces.
- Textiles are sewn with double stitch seams for classic detailing and long lasting quality.
- Wood frames are available in 29 wood finish options to coordinate with our Caseloads, Reception and Table models.
- Find inspiration for upholstery options with our [Textile Program](#).

Certifications & Compliance

- Intertek Sustainability Certified for compliance with VOC emission concentrations
- BIFMA level® Certified for environmentally-preferable and socially-responsible office furniture
- Meets or exceeds ANSI/BIFMA performance standards

Dimensions



Guest Chair Models: 516, 517, 519

Seat Width	20"	Seat Depth	18½"	Seat Hgt	18½"	Arm Height	26½"	Ship Wgt	28lbs
Chair Width	23"	Chair Depth	24"	Chair Hgt	33½"			Cubes	16.9

